

ICO300-83B NEW

Robust DIN-rail Fanless Embedded System with Intel® Celeron® Processor N3350/
Pentium® Processor N4200, Isolated COM, LAN and DIO

Features


- Cost-effective with fanless and cableless design
- Intel® Celeron® processor N3350/Pentium® processor N4200
- 2 or 4 isolated COM ports, 4 USB, 2 GbE LAN
- 8-bit programmable DIO for IoT gateway applications
- Wide operating temperature range from -40°C to +70°C
- 12 ~ 24 VDC wide range power input
- OVP, UVP, OCP, RPP power protection design
- AXView 2.0 intelligent embedded monitoring software for IIoT



▲ Front view



▲ Rear view



▲ Top view



Specifications

Standard Color	Silver																
Construction	Extruded aluminum and heavy-duty steel, IP40																
CPU	Intel® Celeron® processor N3350 (1.1 GHz, Dual Core) Intel® Pentium® processor N4200 (1.1 GHz, Quad Core) (By request)																
System Board	SBC8783B																
System Memory	1 x DDR3L-1866 SO-DIMM, up to 8GB																
BIOS	AMI UEFI BIOS																
System I/O Outlet	<table border="0"> <tr> <td>Serial Port</td> <td>4 x isolated RS-232/422/485 (ICO300-83B-4I COM) 2 x isolated RS-232/422/485 (ICO300-83B-2I COM) 4 x RS-232/422/485 (ICO300-83B-4 COM) COM port support High-speed mode up to 1.5M baud rate Interface select by BIOS Supports Auto Flow Control in RS-485 mode</td> </tr> <tr> <td>USB</td> <td>4 x USB 3.0</td> </tr> <tr> <td>RTC</td> <td>Battery onboard</td> </tr> <tr> <td>Storage</td> <td>2.5" 7/9.5 mm SATA drive mSATA shared with mPCIe slot</td> </tr> <tr> <td>LAN</td> <td>2 x 10/100/1000 Mbps Ethernet (Intel® i211AT for ICO300-83B) (Intel® i210IT for ICO300-83B-WT)</td> </tr> <tr> <td>Display</td> <td>1 x VGA or 1 x HDMI (optional)</td> </tr> <tr> <td>DIO (ICO300-83B-DIO)</td> <td>1 x DI/DO (8-bit programmable, DB9 female connector) Voltage is 5V TTL-level ESD protection corresponds to IEC6100-4-2 (± 8KV (Air); ± 4KV (contact)) Programming: I/O sink current is 10mA (max.) Input/output can be programming</td> </tr> <tr> <td>Power Input</td> <td>1 x DC power input with terminal block</td> </tr> </table>	Serial Port	4 x isolated RS-232/422/485 (ICO300-83B-4I COM) 2 x isolated RS-232/422/485 (ICO300-83B-2I COM) 4 x RS-232/422/485 (ICO300-83B-4 COM) COM port support High-speed mode up to 1.5M baud rate Interface select by BIOS Supports Auto Flow Control in RS-485 mode	USB	4 x USB 3.0	RTC	Battery onboard	Storage	2.5" 7/9.5 mm SATA drive mSATA shared with mPCIe slot	LAN	2 x 10/100/1000 Mbps Ethernet (Intel® i211AT for ICO300-83B) (Intel® i210IT for ICO300-83B-WT)	Display	1 x VGA or 1 x HDMI (optional)	DIO (ICO300-83B-DIO)	1 x DI/DO (8-bit programmable, DB9 female connector) Voltage is 5V TTL-level ESD protection corresponds to IEC6100-4-2 (± 8KV (Air); ± 4KV (contact)) Programming: I/O sink current is 10mA (max.) Input/output can be programming	Power Input	1 x DC power input with terminal block
Serial Port	4 x isolated RS-232/422/485 (ICO300-83B-4I COM) 2 x isolated RS-232/422/485 (ICO300-83B-2I COM) 4 x RS-232/422/485 (ICO300-83B-4 COM) COM port support High-speed mode up to 1.5M baud rate Interface select by BIOS Supports Auto Flow Control in RS-485 mode																
USB	4 x USB 3.0																
RTC	Battery onboard																
Storage	2.5" 7/9.5 mm SATA drive mSATA shared with mPCIe slot																
LAN	2 x 10/100/1000 Mbps Ethernet (Intel® i211AT for ICO300-83B) (Intel® i210IT for ICO300-83B-WT)																
Display	1 x VGA or 1 x HDMI (optional)																
DIO (ICO300-83B-DIO)	1 x DI/DO (8-bit programmable, DB9 female connector) Voltage is 5V TTL-level ESD protection corresponds to IEC6100-4-2 (± 8KV (Air); ± 4KV (contact)) Programming: I/O sink current is 10mA (max.) Input/output can be programming																
Power Input	1 x DC power input with terminal block																

Extension	1 x full-size PCI Express Mini Card slot with SIM slot (For wireless module) 1 x full-size PCI Express Mini Card slot (For wireless module or mSATA)
Watchdog Timer	1 WDT One step is 1 sec, 255 levels
System Indicator	Power, Active
Power Supply	12-24Vdc, 2.82-1.34A (ICO300-83B-N3350) 12-24Vdc, 3.27-1.62A (ICO300-83B-N4200) Protection: OVP (±20%), reverse protection
Operating Temperature	-20°C ~ +70°C (-4°F ~ +158°F) -40°C ~ +70°C (-40°F ~ +158°F) (ICO300-83B-WT)
Humidity	10% ~ 95%
Vibration Endurance	2 Gms (5 ~ 500Hz, amplitude 0.35 mm; operation/storage/transport)
Weight (net/gross)	1.0 kg (2.2 lb)/1.50 kg (3.3 lb)
Certificate	CE, FCC
Dimensions	48 mm (1.88") (W) x 110 mm (4.33") (D) x 155 mm (6.1") (H)
EOS Support	Windows® 10 IoT Linux support package (By Request) AXView 2.0

